

# PLEIAD G4



	Pleiad G4 Flex	Pleiad G4 70	Pleiad G4 125	Pleiad G4 165	Pleiad G4 205	Pleiad G4 Wallwasher	Pleiad G4 Robust	Pleiad G4 Square	Pleiad G4 Surface 128	Pleiad G4 Surface 168	Pleiad G4 Track 128
Ausschnittsmaß (mm)	110	70	125	165	205	165	205	165x165	128	168	128
Deckenstärke	5-50	5-50	5-50	5-50	5-50	0-35		5-50			
Maximale Höhe	110	104	98	98	107	138	125	109	134	154	
Niedriges Lumenoutput (LL)	790-829	790-830	1200	1300	1675	900	1100	1300	1000	1600	1000
Medium Lumenoutput (ML)				1800		1700	1600	1600	1400	2500	
Hohes Lumenoutput (HL)	1400	1280	2350	2800	2800	2500	2600	3500	2400	4500	2700
Extra hohes Lumenoutput (EHL)				3700	5400						
Tiefstrahlend ~ 20°	●	●									
Mittelstrahlend 40-50°	●	●	●	●	●			●	●	●	●
Breitstrahlend >70°			●	●	●		●	●	●	●	●
< UGR 19		●	●	●	●		●	●	●	●	●
< 3000 cd/m²		●	●	●	●		●	●	●	●	●
Farben									weiß oder schwarz	weiß oder schwarz	weiß oder schwarz
Glänzender Reflektor						●					
Matter Reflektor		●	●	●	●	●	●	●	●	●	●
Weißer Reflektor		●	●	●	●			●	●	●	●
Schwarzer Reflektor	●	●	●	●	●			●	●	●	●
2700 K / CRI 98 /SDCM 2		●									
3000 K	●	●	●	●	●	●	●	●	●	●	●
4000 K	●	●	●	●	●	●	●	●	●	●	●
CRI >80	●	●	●	●	●	●	●	●	●	●	●
CRI >90	●	●	●	●	●	●	●	●	●	●	●
SDCM 3	●	●	●	●	●	●	●	●	●	●	●
An/Aus Standard	●	●	●	●	●	●	●	●	●	●	●
DALI/Phase-pulse	●	●	●	●	●	●	●	●	●	●	●
CLO	●	●	●	●	●	●	●	●		●	
	45° schwenkbar 355° drehbar			Tunable White RGB/W Notlicht	Tunable White Notlicht	Tunable White RGB/W Notlicht		Tunable White		Tunable White	Control Track